

Refillable spray-cans

For the propellant - compressed air

The benefits at a glance

- Environmentally friendly
- Economical
- High industrial safety
- Suitable for many sprayable liquids of low viscosity up to a viscosity grade of ISO VG 15



Property

The refillable spray cans are extremely robust and offer highest occupational safety. The bursting pressure is 80 bar. The recommended working pressure 5-8 bar. The handling is very easy and the use reduces the consumption of common spray cans many times over.

Refillable spray cans - handling



Vent the can by opening the union nut.



Remove spray nozzle together with rising pipe. Pour liquid up to the declared filling height, shown on the label.



Insert rising pipe, place spray nozzle upon threaded shoulder and screw up hand tight with coupling ring.



Keep can upside down with the spray nozzle and fill with compressed air through compressor, hand pump or food pump (5-8 bar, depending on the product).

Fields of application

M.T.X. 100

Special cleaner

M.T.X. 60

Special cleaner

M.T.X. 60 forte

Intensive cleaner

M.T.X. Ultra

Power cleaner

S.L.X. Top

High performance electro-cleaner

S.L.X. Super

Electro safety cleaner

F.L. 5 / 12 / 20 / 50

NSF creep and fine oil chain lubricants

K.S.P. 150

Corrosion protection

S.K.D. 16 N

High performance-inside bearing lubricant

O.C.X.


Oxide remover

T.R.S. Plus

Creep oil of first quality

W.S.X.

Moisture protector



Equipment



Air filling station, self-closing, with connecting hose and compressed air-quick couplin.



Self-closing filling adapter, suitable for quick coupling.

Further accessories can be found in our [accessories brochure](#).

| Article No. | Designation |
|-------------|---|
| 800 094 926 | Spray can RED, for Rivolta-Cleaners |
| 800 094 940 | Spray-mounting for cleaners: 1 valve, 2 spray nozzles, 2 rising pipes |
| 800 094 964 | Air filling station, self-closing, with connecting hose and compressed air-quick coupling |
| 800 094 933 | Spray can GREEN, for Rivolta-Spray oils |
| 800 094 957 | Spray-mounting for spray oils: 1 valve, 2 spray nozzles, 2 rising pipes |
| 800 094 971 | Self-closing filling adapter, suitable for quick coupling |



Bremer & Leguil GmbH

Am Burgacker 30-42 • 47051 Duisburg • Germany

Tel. +49 203 99 23-0 • Fax +49 203 2 59 01

info@bremer-leguil.de

This text contains facts and statements and is determined with our best knowledge and will be checked continuously. These statements are depending - among other reasons - on experiences gained in the industry. We only pass them on without liability. Before using our products you should test the applicability and you should convince yourself about the satisfactory performance. Our application examples and suggestions should not request to violate patent rights. Product illustrations partly consist of picture compositions and therefore, do not necessarily reflect the reality.

V231108