

S.L.X. Top

High-performance electro cleaner



The benefits at a glance

- NSF-K2 listed
- Dielectric strength > 150,000 volt/cm
- High cleaning effect
- Evaporation without residues
- Compatible with metals and materials resistant to solvents
- Practically odourless



Properties

Rivolta S.L.X. Top is a high performance cleaner with special active ingredients for the use at electric and electronic installations, components and devices which are disconnected from voltage. The high dielectric strength (> 150,000 V/cm) allows a safe cleaning without dismantling the electrical single components. Before restarting the installations the cleaning liquid needs to be evaporated completely.

Medium fast evaporation. The cleaner does not leave any disturbing residues, the adhesion of new dirt is prevented. The short drying time saves labour times.

Excellently compatible with metals as well as materials which are resistant to solvents, e.g. paints, plastics and elastomers. The liquid medium reaches inaccessible areas in installations. The cleanser rinses the components holistically and dissolves oil, grease and dusty impurities. The resistance value of insulating materials and/or conductivity of e.g. contacts etc. are improved or restored.

Fields of application

Rivolta S.L.X. Top is used for the cleaning of electric and electronic installations and devices such as e.g.: generators, trans-

formers, rectifiers, electric motors, electrical switch gears and devices, electrical equipment for vehicles and machines, installations and devices of the radio and television engineering, insulators and contact rails, electronic components, printed circuit boards, potentiometers, counters, time switches etc.

Instructions for use


Easy application by spraying with a spray can. For bigger installations the use of bulk material (e.g. 10 L can) in combination with **B&L high pressure cleaning device** is recommended. The powerful device additionally supports the high chemical cleaning performance in a physical way. As the product is odourless a pleasant processing is realized.

Suitable application devices and accessories in our [accessories brochure](#).

Attention

Do **not** saturate carbon brushes in engines or generators with cleaning liquid. Do **not** use product on units which are still under voltage. Risk of fire ignited by sparks. Prior to reconnection the complete evaporation of the product has to be ensured.

Form	liquid
Colour	transparent
Odour	neutral



Available in:

- 400 ml spray can (PU 12 pcs.)
- 1 l bottle
- cans (10 l and 20 l)
- drums (60 l and 200 l)

	Value	Norm
NSF Reg.-Nr.	137308 / 137307 (Spray)	-
Evaporation	without residues	-
Evaporation rate	60	DIN 53170
Flash point	> +60 °C	DIN EN ISO 2719
Dielectric strength	> 150.000 Volt/cm	DIN EN 60156



Bremer & Leguil GmbH
Am Burgacker 30-42 • 47051 Duisburg • Germany
Tel. +49 203 99 23-0 • Fax +49 203 2 59 01
info@bremer-leguil.de

This text contains facts and statements and is determined with our best knowledge and will be checked continuously. These statements are depending - among other reasons - on experiences gained in the industry. We only pass them on without liability. Before using our products you should test the applicability and you should convince yourself of the satisfactory performance. Our application examples and suggestions should not request to violate patent rights. Product illustrations partly consist of picture compositions and therefore, do not necessarily reflect the reality.

V230807