

SAFETY DATA SHEET

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name: Rivolta W.A.P. Spray

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses: Lubricant

Uses advised against:No uses advised against identified.

1.3 Details of the supplier of the safety data sheet

Manufacturer / Supplier Bremer & Leguil GmbH

Am Burgacker 30 - 42 47051 Duisburg / Germany info@bremer-leguil.de

Telephone: +49(0)203/9923-0

Contact Person: Bremer & Leguil GmbH - Product Safety Management

E-mail: product-safety@bremer-leguil.de

1.4 Emergency telephone number: +49 (0)613119240 (Giftinformationszentrum Mainz 00:00-24:00)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

The product has been classified and labelled as hazardous according to regulation (EU) 1272/2008 (CLP).

Classification according to Regulation (EC) No 1272/2008 as amended.

Physical Hazards

Aerosol Category 1 H222: Extremely flammable aerosol.

H229: Pressurized container: May burst if heated.

Health Hazards

Serious eye damage Category 1 H318: Causes serious eye damage.

Environmental Hazards

Chronic hazards to the aquatic Category 3 H412: Harmful to aquatic life with long lasting

environment effects.

Hazard summary

Physical Hazards: Flammable aerosol.

2.2 Label Elements

Contains: Lime hydrate

Revision Date: 30.11.2023 Version: 5.0





Signal Words: Danger

Hazard Statement(s): H222: Extremely flammable aerosol.

H229: Pressurized container: May burst if heated.

H318: Causes serious eye damage.

H412: Harmful to aquatic life with long lasting effects.

Precautionary Statements

Prevention: P102: Keep out of reach of children.

P210: Keep away from heat, hot surfaces, sparks, open flames and

other ignition sources. No smoking.

P211: Do not spray on an open flame or other ignition source.

P251: Do not pierce or burn, even after use. P273: Avoid release to the environment.

P280: Wear protective gloves/ protective clothing/ eye protection/ face

protection.

Response: P305+P351+P338: IF IN EYES: Rinse cautiously with water for several

minutes. Remove contact lenses, if present and easy to do. Continue

rinsing.

P310: Immediately call a POISON CENTER or doctor/ physician.

Storage: P410+P412: Protect from sunlight. Do not expose to temperatures

exceeding 50 °C/122°F.

Disposal: P501: Dispose of contents/ container to an approved facility in accord-

ance with local, regional, national and international regulations.

2.3 Information on other haz-

ards

By handling of mineral oil products and chemical products no particular hazard is known when normal precautions (item 7) and personal protective equipment (item 8) are kept. The product may not be released into the envi-

ronment without control.

Endocrine disrupting prop-

erties

The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation

(EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

General information: Mixture of components with propellant in aerosol can. Mixture of active

ingredients with propellant

Revision Date: 30.11.2023 Version: 5.0



| Chemical name | Identifier | Concentration * | REACH Registra- tion No. | Notes |
|---------------------------------|-------------------|------------------|-----------------------------|-------|
| Propane | EINECS: 200-827-9 | 0% - <100,00% | 01-2119486944-21 | |
| Butane (<0,1% 1,3-butadiene) | EINECS: 203-448-7 | 0% - <100,00% | 01-2119474691-32 | |
| Isobutane (<0,1% 1,3-butadiene) | EINECS: 200-857-2 | 0% - <100,00% | 01-2119485395-27 | |
| Hydrocarbons, low viscous | EC: 927-241-2 | 10,00% - <20,00% | 01-2119471843-32 | |
| Lime hydrate | EINECS: 215-137-3 | 5,00% - <10,00% | 01-2119475151-45 | |
| inorganic Zink salt | EINECS: 231-203-4 | 1,00% - <2,50% | 01-2120768152-56 | |
| Calcium Sulfonate | EINECS: 271-529-4 | 0,10% - <1,00% | 01-2119492627-25 | |
| Calcium Sulfonate | EINECS: 263-093-9 | 0,10% - <1,00% | 01-2119488992-18 | |
| Ca Sulfonate | EINECS: 274-263-7 | 0,10% - <1,00% | 01-2119492616-28 | |
| Triaryl phosphate, alkylated | EC: 700-990-0 | 0,10% - <1,00% | 01-2119519251-50 | |

^{*} All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume. PBT: persistent, bioaccumulative and toxic substance.

Classification

| Chemical name | e Identifier Classification | | ification |
|---------------------------------|-----------------------------|------|----------------------------------------------------------------------------------------------------------|
| Propane | EINECS: 200-827-9 | CLP: | Flam. Gas 1A;H220, Press. Gas Compr. Gas;H280 |
| Butane (<0,1% 1,3-butadiene) | EINECS: 203-448-7 | CLP: | Flam. Gas 1A;H220, Press. Gas Compr. Gas;H280 |
| Isobutane (<0,1% 1,3-butadiene) | EINECS: 200-857-2 | CLP: | Flam. Gas 1A;H220, Press. Gas Compr. Gas;H280 |
| Hydrocarbons, low viscous | EC: 927-241-2 | CLP: | Flam. Liq. 3;H226, Asp. Tox. 1;H304, STOT SE 3;H336, Aquatic Chronic 3;H412 EUH066 |
| Lime hydrate | EINECS: 215-137-3 | CLP: | Eye Dam. 1;H318, STOT SE 3;H335, Skin Irrit. 2;H315 |
| inorganic Zink salt | EINECS: 231-203-4 | CLP: | Aquatic Chronic 1;H410, Aquatic Acute 1;H400 |
| Calcium Sulfonate | EINECS: 271-529-4 | CLP: | Skin Sens. 1B;H317 |
| Calcium Sulfonate | EINECS: 263-093-9 | CLP: | Skin Sens. 1B;H317 |
| Ca Sulfonate | EINECS: 274-263-7 | CLP: | Skin Sens. 1B;H317 |
| Triaryl phosphate, alkylated | EC: 700-990-0 | CLP: | Aquatic Acute 1;H400, Aquatic Chronic 2;H411; M-Factor (aquatic acute): 1; M-Factor (aquatic chronic): 1 |

CLP: Regulation No. 1272/2008.

specific concentration limit

| Chemical name | Identifier | specific concentra- tion limit | Hazard class | Category | Hazard state- ments |
|-------------------|-------------------|--------------------------------------|-----------------|----------|---------------------------|
| Calcium Sulfonate | EINECS: 271-529-4 | >= 10 % | Skin sensitizer | 1B | H317 |
| Calcium Sulfonate | EINECS: 263-093-9 | >= 10 % | Skin sensitizer | 1B | H317 |
| Ca Sulfonate | EINECS: 274-263-7 | >= 10 % | Skin sensitizer | 1B | H317 |

For the wording of the listed hazard statements refer to section 16.

SECTION 4: First aid measures

General: Instantly remove any clothing soiled by the product.

Revision Date: 30.11.2023 Version: 5.0

vPvB: very persistent and very bioaccumulative substance.



4.1 Description of first aid measures

Inhalation: Supply fresh air; consult doctor in case of symptoms.

Eye contact: Immediately flush with plenty of water for at least 15 minutes. If easy to do,

remove contact lenses. Get medical attention.

Skin Contact: Wash with soap and water.

Ingestion: Rinse mouth thoroughly.

4.2 Most important symptoms and effects, both acute and delayed:

Risk of serious damage to eyes. Dizziness Freeze burns

4.3 Indication of any immediate medical attention and special treatment needed

Get medical attention if symptoms occur.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing me-

dia:

CO2, fire extinguishing powder or fog like water spraying. Extinguish larger fires with alcohol resistant foam or spray water with suitable surfactant add-

ed

Unsuitable extinguishing

media:

Water with a full water jet.

5.2 Special hazards arising from the substance or mix-

ture:

Danger of explosion with aerosol cans.

5.3 Advice for firefighters

Special fire-fighting proce-

dures:

Move container from fire area if it can be done without risk. Dispose of fire debris and contaminated fire fighting water inaccordance with official regulations. Collect contaminated fire fighting water separately. It must not enter

drains.

Special protective equipment for fire-fighters:

Self-contained breathing apparatus and full protective clothing must be

worn in case of fire.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures:

Keep away from sources of ignition - No smoking.

6.2 Environmental Precautions: Avoid release to the environment. Prevent further leakage or spillage if safe

to do so. Avoid release to the environment. Prevent further leakage or spill-

age if safe to do so.

6.3 Methods and material for containment and cleaning

up:

Scrape up spillage or absorb with absorbing material. Stop the flow of material, if this is without risk. Dispose of the material collected according to

regulations.

Revision Date: 30.11.2023 Version: 5.0



6.4 Reference to other sections:

See Section 8 of the SDS for Personal Protective Equipment. See Section 7 for information on safe handling See Section 13 for information on disposal.

Dike for later disposal. Prevent entry into waterways, sewer, basements or confined areas. Stop the flow of material, if this is without risk.

SECTION 7: Handling and storage:

7.1 Precautions for safe handling:

Avoid contact with flame and heat source, prevent contact with direct sunlight Use only in well-ventilated areas.

7.2 Conditions for safe storage, including any incompatibilities:

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use. Local regulations concerning handling and storage of waterpolluting products have to be followed. Local regulations for the storage and handling of aerosol cans and flammable liquids have to be kept. Keep away from heat/sparks/hot surfaces. - No smoking. Local regulations concerning handling and storage of waterpolluting products have to be followed. Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use. Local regulations for the storage and handling of aerosol cans and flammable liquids have to be kept. Keep away from heat/sparks/hot surfaces. - No smoking.

7.3 Specific end use(s): Not applicable

Storage Class: 2 B, Aerosols

SECTION 8: Exposure controls/personal protection

8.1 Control Parameters

Occupational Exposure Limits

| Chemical name | Туре | Exposure Limit V | /alues | Source |
|-------------------------------------|------|------------------|-----------|-----------------------------------------------------------------------------|
| Propane | AGW | 1.000 ppm 1.8 | 800 mg/m3 | Germany. TRGS 900, Occupational Exposure Limits (AGW), as amended (01 2012) |
| Butane (<0,1% 1,3- butadiene) | AGW | 1.000 ppm 2.4 | 00 mg/m3 | Germany. TRGS 900, Occupational Exposure Limits (AGW), as amended (01 2012) |
| Isobutane (<0,1% 1,3- butadiene) | AGW | 1.000 ppm 2.4 | 00 mg/m3 | Germany. TRGS 900, Occupational Exposure Limits (AGW), as amended (01 2012) |
| Hydrocarbons, low viscous | AGW | 6 | 600 mg/m3 | Germany. TRGS 900, Occupational Exposure Limits (AGW), as amended |

8.2 Exposure controls

Appropriate engineering controls:

Provide adequate ventilation. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment

Revision Date: 30.11.2023 Version: 5.0



General information: Wash hands before breaks and after work. Use personal protective equip-

ment as required. Personal protection equipment should be chosen according to the CEN standards and in discussion with the supplier of the personal protective equipment. The usual precautionary measures should be ad-

hered to inhandling the chemicals or the mineral oil products.

Eye/face protection: Avoid contact with skin and eyes. Goggles/face shield are recommended. If

risk of splashing, wear safety goggles or face shield. Wear eye protec-

tion/face protection. Avoid contact with skin and eyes.

Skin protection

Hand Protection: Material: Nitrile butyl rubber (NBR).

Min. Breakthrough time: >= 480 min

Recommended thickness of the material: >= 0,38 mm

Avoid long-term and repeated skin contact. Suitable gloves can be recommended by the glove supplier. Use skin protection cream for preventive skin protection. Protective gloves, where permitted in acc. to safety directions. The exact break through time has to be found out by the manufactur-

er of the protective gloves and has to be observed.

Other: Do not carry cleaning cloths impregnated with the product in trouser pock-

ets. Wear suitable protective clothing.

Respiratory Protection: Ensure good ventilation/exhaustion at the workplace. Avoid breathing va-

pour/ aerosol.

Thermal hazards: Not known.

Hygiene measures: Always observe good personal hygiene measures, such as washing after

handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing to remove contaminants. Discard contaminated foot-

wear that cannot be cleaned.

Environmental Controls: No data available.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

Physical state:AerosolForm:AerosolColor:Beige

Odor: Characteristic

pH: substance/mixture is non-soluble (in water)

Freezing point: not determined not determined

Flash Point: < 0 °C

Evaporation Rate: Not applicable for mixtures

Flammability (solid, gas): not determined

Explosion Limit - Upper (%):

Explosion Limit - Lower (%):

Vapor pressure:

Not applicable for mixtures

Not applicable for mixtures

Revision Date: 30.11.2023 Version: 5.0



Relative vapor density:Not applicable for mixtures **Density:**0,70 - 0,75 g/cm3 (20 °C)

Solubility(ies)

Solubility in Water: The product is insoluble in water.

Solubility (other): No data available.

Partition coefficient (n-octanol/water): Not applicable for mixtures

Auto-ignition temperature: not determined not determined

Kinematic viscosity: > 20,5 mm2/s (40 °C)

Explosive properties:Value not relevant for classification **Oxidizing properties:**Value not relevant for classification

Particle characteristics:Not applicable9.2 Other informationNo data available.

SECTION 10: Stability and reactivity

10.1 Reactivity: Stable under normal use conditions.

10.2 Chemical Stability: Stable under normal use conditions.

10.3 Possibility of hazardous

reactions:

Stable under normal use conditions.

10.4 Conditions to avoid: Stable under normal use conditions.

10.5 Incompatible Materials: Strong oxidizing substances. Strong acids. Strong bases.

10.6 Hazardous Decomposition

Products:

Thermal decomposition or combustion may liberate carbon oxides and oth-

er toxic gases or vapors.

SECTION 11: Toxicological information

Information on likely routes of exposure

Inhalation: No data available.

Ingestion: No data available.

Skin Contact: No data available.

Eye contact: Causes serious eye damage.

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Oral

Product: Not classified for acute toxicity based on available data.

Revision Date: 30.11.2023 Version: 5.0



Specified substance(s)

Hydrocarbons, low vis-

cous

LD 50 (Rat): > 5.001 mg/kg (OECD 401)

Lime hydrate LD 50 (Rat): 7.340 mg/kg

Calcium Sulfonate LD 50 (Rat): > 5.001 mg/kg

Calcium Sulfonate LD 50 (Rat): > 16.000 mg/kg

Ca Sulfonate LD 50 (Rat): > 5.000 mg/kg (OECD 401)

Triaryl phosphate, alkyl-

ated

LD 50 (Rat): > 5.001 mg/kg

Dermal

Product: Not classified for acute toxicity based on available data.

Specified substance(s)

Hydrocarbons, low vis-

cous

LD 50 (Rabbit): > 5.001 mg/kg (OECD 402)

Calcium Sulfonate LD 50 (Rabbit): > 5.001 mg/kg

Gas

Calcium Sulfonate LD 50 (Rat): > 5.001 mg/kg

Ca Sulfonate LD 50 (Rabbit): > 5.000 mg/kg (OECD 402)

Inhalation

Product: Not classified for acute toxicity based on available data.

Specified substance(s)

Butane (<0,1% 1,3-

LC 50 (Rat, 4 h): 658 mg/l

butadiene)

Skin Corrosion/Irritation:

Product: Specified substance(s) Based on available data, the classification criteria are not met.

Hydrocarbons, low vis-

cous

OECD 404 Prolonged or repeated contact:

Slightly irritating.

Calcium Sulfonate OECD 404 (Rabbit):

Not irritant.

Calcium Sulfonate OECD 404 (Rabbit):

Not irritant.

Ca Sulfonate OECD 404 (Rabbit):

Not irritant.

Revision Date: 30.11.2023 Version: 5.0



Serious Eye Damage/Eye Irritation:

Product: Based on available data, the classification criteria are met.

Specified substance(s)

Calcium Sulfonate OECD 405 (Rabbit):

Not irritant.

Respiratory or Skin Sensitization:

Product: Skin sensitizer: Based on available data, the classification criteria are not

met.

Respiratory sensitizer: Based on available data, the classification criteria

are not met.

Specified substance(s)

Hydrocarbons, low vis-

cous No sensitizing effect (guinea pig); OECD 406

Calcium Sulfonate

May cause sensitization by skin contact.

Calcium Sulfonate

May cause sensitization by skin contact.

Ca Sulfonate

May cause sensitization by skin contact.

Germ Cell Mutagenicity

Product: Based on available data, the classification criteria are not met.

Carcinogenicity

Product: Based on available data, the classification criteria are not met.

Reproductive toxicity

Product: Based on available data, the classification criteria are not met.

Specific Target Organ Toxicity - Single Exposure

Product: Based on available data, the classification criteria are not met.

Specific Target Organ Toxicity - Repeated Exposure

Product: Based on available data, the classification criteria are not met.

Aspiration Hazard

Product: Based on available data, the classification criteria are not met.

11.2 Information on other haz-

ards

Endocrine disrupting properties

Product: The substance/mixture does not contain components considered to have

endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation

9/14

(EU) 2018/605 at levels of 0.1% or higher.

Revision Date: 30.11.2023 Version: 5.0

Print date: 07.05.2025

SDS_DE - EN - CP1008696



SECTION 12: Ecological information

General information: Not applicable Not applicable

12.1 Toxicity

Acute toxicity

Product: Based on available data, the classification criteria are not met.

Fish

Specified substance(s)

Propane LC 50 (Fish, 96 h): > 1.000 mg/l

Isobutane (<0,1% 1,3-

butadiene)

LC 50 (Fish, 96 h): 28 mg/l

Hydrocarbons, low vis-

cous

LC 50 (Fish, 96 h): > 10 - 30 mg/l

Lime hydrate LC 50 (Fish, 96 h): 50,6 mg/l (OECD 203)

Calcium Sulfonate LL 50 (Cyprinodon variegatus, 96 h): > 10.000 mg/l (OECD 203)

Calcium Sulfonate LC 50 (Fish, 96 h): > 10.000 mg/l (OECD 203)

Ca Sulfonate LC 50 (Fish, 96 h): > 1.001 mg/l (OECD 203)

Triaryl phosphate, alkyl-

ated

LC 50 (Fish, 96 h): 0,8 mg/l

Aquatic Invertebrates Specified substance(s)

Isobutane (<0,1% 1,3-

butadiene)

EC 50 (Water Flea, 48 h): 16,3 mg/l

Hydrocarbons, low vis-

cous

EC 50 (Water Flea, 48 h): > 22 - 46 mg/l

Lime hydrate EC 50 (Water Flea, 48 h): 49,1 mg/l (OECD 202)

inorganic Zink salt EC 50 (Water Flea, 48 h): 26 mg/l

Calcium Sulfonate EL50 (Daphnia magna, 48 h): > 1.000 mg/l

Calcium Sulfonate EC 50 (Water Flea, 48 h): > 100 mg/l (OECD 202)

Ca Sulfonate EC 50 (Water Flea, 48 h): > 1.001 mg/l

Triaryl phosphate, alkyl-

ated

EC 50 (Water Flea, 48 h): 0,202 mg/l

Chronic ToxicityProduct: Based on available data, the classification criteria are met.

Fish

Specified substance(s)

Triaryl phosphate, alkyl- NOEC (Fish, 90 d): 0,093 mg/l

Revision Date: 30.11.2023 Version: 5.0



ated

Aquatic Invertebrates Specified substance(s)

Lime hydrate NOEC (Water Flea, 14 d): 32 mg/l

Triaryl phosphate, alkyl-

ated

NOEC (Water Flea, 21 d): 0,0399 mg/l

Toxicity to Aquatic Plants Specified substance(s)

Isobutane (<0,1% 1,3-

butadiene)

EC 50 (Alga, 72 h): 8,6 mg/l

Hydrocarbons, low vis-

cous

EC 50 (Alga, 72 h): > 1.000 mg/l

Lime hydrate NOEC (Alga, 72 h): 48 mg/l

EC 50 (Alga, 72 h): 184,57 mg/l

inorganic Zink salt EC 50 (Algae, 72 h): 0,233 mg/l (OECD 201)

Calcium Sulfonate EL50 (Algae (Pseudokirchneriella subcapitata), 96 h): > 1.000 mg/l

Ca Sulfonate EC 50 (Alga, 72 h): > 1.000 mg/l

Triaryl phosphate, alkyl-

ated

EC 50 (Alga, 72 h): 1,4 mg/l NOEC (Alga, 72 h): 0,05 mg/l

12.2 Persistence and Degradability

Biodegradation

Product: Not applicable for mixtures

Specified substance(s)

Hydrocarbons, low vis-

cous

89 % (28 d) The product is easily biodegradable.

Calcium Sulfonate 8,6 % (28 d) Not easily biodegradable

Triaryl phosphate, alkyl-

ated

61 % (28 d) Readily biodegradable

12.3 Bioaccumulative potential

Product: Not

Not applicable for mixtures

12.4 Mobility in soil:

Product: Not applicable for mixtures

12.5 Results of PBT and vPvB

assessment:

The product does not contain any substances fulfilling the PBT/vPvB criteria.

11/14

Revision Date: 30.11.2023 Version: 5.0

Print date: 07.05.2025

SDS_DE - EN - CP1008696



12.6 Endocrine disrupting properties

Product: The substance/mixture does not contain components considered to have

endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation

(EU) 2018/605 at levels of 0.1% or higher.

12.7 Other adverse effects: Harmful to aquatic life with long lasting effects.

Water Hazard Class

(WGK):

WGK 1: slightly water-endangering.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

General information: Dispose in accordance with all applicable regulations.

Disposal methods: Discharge, treatment, or disposal may be subject to national, state, or local

laws.

European Waste Codes

16 05 04*: Gases in pressure containers (including halons) containing

hazardous substances.

SECTION 14: Transport information

ADR/RID

14.1 UN number or ID number: UN 195014.2 UN Proper Shipping Name: AEROSOLS

14.3 Transport Hazard Class(es)

Class: 2
Label(s): 2.1
Hazard No. (ADR): Tunnel restriction code: (D)

14.4 Packing Group: 14.5 Environmental hazards: 14.6 Special precautions for user: -

IMDG

14.1 UN number or ID number: UN 195014.2 UN Proper Shipping Name: AEROSOLS

14.3 Transport Hazard Class(es)

 Class:
 2.1

 Label(s):
 2.1

 EmS No.:
 F-D, S-U

14.3 Packing Group: –14.5 Environmental hazards: –14.6 Special precautions for user: –

Revision Date: 30.11.2023 Version: 5.0



IATA

14.1 UN number or ID number: UN 1950

14.2 Proper Shipping Name: Aerosols, flammable

14.3 Transport Hazard Class(es):

Class: 2.1
Label(s): 2.1

14.4 Packing Group: 14.5 Environmental hazards: 14.6 Special precautions for user: -

14.7 Maritime transport in bulk according to IMO instruments: Not applicable.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

EU Regulations

EU. Regulation 1005/2009/EC on substances that deplete the ozone layer, Annex I, Controlled Substances: none

EU. Regulation 2019/1021/EU on persistent organic pollutants (POPs) (recast), as amended: none

Regulation (EC) No. 649/2012 Import and export of dangerous chemicals: none

National Regulations

Water Hazard Class

(WGK):

WGK 1: slightly water-endangering.

15.2 Chemical safety as-

sessment:

No Chemical Safety Assessment has been carried out.

DIRECTIVE 2012/18/EU (SEVESO III) on the control of major-accident hazards involving dangerous substances

| Hazard category in accordance with Regulation (EC) No 1272/2008 | Qualifying quantity for the application of Lower-tier requirements: | Qualifying quantity for the application of Upper-tier requirements: | |
|-----------------------------------------------------------------|---------------------------------------------------------------------|---------------------------------------------------------------------|--|
| | | | |

SECTION 16: Other information

Revision Information: Vertical lines in the margin indicate an amendment.

Revision Date: 30.11.2023 Version: 5.0



Wording of the H-statements in section 2 and 3

EUH066 Repeated exposure may cause skin dryness or cracking.

H220 Extremely flammable gas.
H222 Extremely flammable aerosol.
H226 Flammable liquid and vapor.

H229 Pressurized container: May burst if heated.

H280 Contains gas under pressure; may explode if heated.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.
 H318 Causes serious eye damage.
 H335 May cause respiratory irritation.
 H336 May cause drowsiness or dizziness.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.
 H411 Toxic to aquatic life with long lasting effects.
 H412 Harmful to aquatic life with long lasting effects.

Other information: The classification complies with the current EU lists; however, it has been

supplemented with expert literature information and information provided by/about our company. The following evaluation methods were used: - On the basis of test data - Calculation Method - Bridging Principle "Substantially simi-

lar mixtures" - Expert Judgement

Revision Date: 30.11.2023

Disclaimer: The data contained in this safety data sheet are based on our current

knowledge and experience and are given to the best of our knowledge and belief. It characterizes the product only with regard to safety requirements for handling, transport and disposal. The data do not describe the product's properties (tech. product specification). Neither should any agreed property nor the suitability of the product for any specific technical application be deduced from the data contained in this safety data sheet. Modifications on this document are not allowed. The data are not transferable to other products. In the case of mixing the product with other products or in the case of processing, the data in this safety data sheet are not necessarily valid for the new-made material. It is the responsibility of the recipient of the product to observe federal, state and local law. Please contact us to obtain up-to-date safety data sheets. This document was issued electronically and has no sig-

nature.

Revision Date: 30.11.2023 Version: 5.0

Print date: 07.05.2025